



antenall



UBIQUITI
NETWORKS

AKTIVNA MREŽNA OPREMA

UBIQUITI CENOVNIK

Važi od: 27.04.2024.



ANTENALL DOO









Ljiljane Krstić 24, Zemun-Altina

tel: 011/6356356

office@antenall.rs

www.antenall.rs

UBIQUITI - MREŽNA OPREMA

NAZIV ARTIKLA	Kat. br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (racun bez PDV)
<p>Ubiquiti U6+</p>  	8496	<p>Ubiquiti U6+ WiFi frekvencija: Dual Band Vrsta antene: Interna Protok: -2.4 GHz - 573.5 Mbps -5 GHz -2402 Mbps Vrsta LAN Portova (Mbit): 1000 Broj LAN Portova: 1 PoE In: Da Napajanje: PoE, PoE adapter (nije uključen) Potrošnja: 9W Radna temperatura: -30 to 60° C Dimenzije: Ø160 x 32.65 mm</p>	195,60	163,00
<p>UniFi U6-PRO</p>  	7674	<p>UniFi U6-PRO Dual-band WiFi (802.11ax) WiFi standardi: 802.11a/b/g, WiFi 4/WiFi 5/WiFi 6 Interfejs: internet ,bluetooth Vrsta antene: Interna Maksimalna potrošnja: 13W MIMO: 4x4 na 2.4 GHz i 5 GHz Napajanje: UniFi PoE switch 48V, 0.5A PoE adapter Dimenzije: Ø197 x 35mm Radna temperatura: -30 to 60° C</p>	306,00	255,00
<p>UniFi U6-LR</p>  	7618	<p>UniFi U6-LR UniFi Access Point WiFi 6 Long-range Interfejs: internet ,bluetooth Vrsta antene: Interna Jačina signala: 20 dBm Maksimalna potrošnja: 16,5W MIMO: 4x4 na 2.4 GHz i 5 GHz Napajanje: UniFi PoE switch 48V, 0.5A PoE adapter Dimenzije: 200 x 200 x 48 mm Radna temperatura: -30 to 60° C</p>	342,00	285,00
<p>UniFi Outdoor AP AC Mesh PRO</p>  	7936	<p>UniFi Outdoor AP AC Mesh PRO Interface: 2 x 10/100/1000 Ethernet Ports WiFi frekvencija: Dual Band WiFi brzina: 2.4 GHz - 450 Mbps, 5 GHz - 1.3 Gbps Vrsta antene: Interna Izmenjiva antena: Ne Broj antena: 3 x Internna Dual-Band Antena 8 dBi Jačina signala: 22 dBm Dometa: 183 m Vrsta LAN Portova (Mbit): 1000 Broj LAN Portova: 2 PoE In: 802.3af PoE Napajanje: 48V, 0.5A PoE Gigabitni Adapter Dimenzije: 343.2 x 181.2 x 60.2 mm Radna temperatura: -40 do 70° C Težina: 633 g</p>	320,40	267,00

**Extralink POE-48-48W 1A
Power Adapter Ac Cable**



8301

Extralink POE-48-48W 1A Power Adapter Ac Cable

Napajanje ima kabl za napajanje dužine 1,2 metra koji se završava tipičnim računarskim konektorom tipa C14 i ima dva RJ45 porta. Jedan od njih povezuje uređaj koji treba da se napaja, a drugi se koristi za patchcord vezu sa prekidačem ili ruterom.

Ulazna voltaža: 110/220V
Izlazna voltaža: 48.0V
Vrsta LAN portova (Mbitortova (Mbit): 1000
Broj LAN portova: 2

LED indikator pokazuje ispravan rad uređaja. Ako se aktivira jedna od sledećih zaštita: **zaštita od kratkog spoja ili preopterećenja**, napajanje prekida napajanje uređaja. Nakon što kvar prestane, napajanje će se automatski pokrenuti.

17,80

14,83

UCK-G2 PLUS



7497

UCK-G2 PLUS

Procesor: Quad core Arm® Cortex®-A53 based chip
Radni takt procesora: 2 GB RAM
eMMC Memorija: 32 GB
Hard disk: 1 tb 2.5"SATA HDD

Kapacitet : UniFi Protect mode:

Up to 20 G3 cameras
Up to 10 G4 cameras UniFi SDN + UniFi Protect:
Up to 15 G3 cameras and 50 UniFi devices
Up to 7 G4 cameras

Vrsta LAN Portova (Mbit): 1000

Broj LAN Portova: 1

LED: (1) Power, White/Blue

PoE In: Da

Napajanje: 802.3af PoE

Quick charge 2.0/3.0 power adapter, 9VDC, 2A

Radna temperatura: 0 to 35° C

327,60

273,00

**LiteBeam AC, LBE-5AC-
Gen2**



6744

LiteBeam AC, LBE-5AC-Gen2

WiFi frekvencija: Dual Band

Vrsta antene: Eksterna

Jačina signala: 23 dBi

Izmenjiva antena: Ne

PoE In: Da

Napajanje: 24V, 0.3A Gigabit PoE Adapter (Included)

Frekvencija: 5150 - 5875 MHz

Procesor: MIPS 74Kc

Memorija: 64 MB DDR2

LED: Power, Ethernet

Dimenzije: 358 x 271.95 x 272.5 mm

Težina: 800 g

117,60

98,00

LBE-5AC-LR



7222

LBE-5AC-LR

WiFi frekvencija: Dual Band

Vrsta antene: Eksterna

Jačina signala: 26 dBi

Izmenjiva antena: Ne

PoE In: Da

Napajanje: 24V, 0.3A Gigabit PoE Adapter (Included)

Frekvencija: 5150 - 5875 MHz

Procesor: MIPS 74Kc

Memorija: 64 MB DDR2

LED: Power, Ethernet

Dimenzije: 512.5 x 385.75 x 258.3 mm

Težina: 1.360 kg

204,00

170,00

UniFi UMA-D

7214

UniFi UMA-D

UniFi antena UMA-D je dizajnirana za rad sa UniFi® AC Mesh AP, model UAP-AC-M. Sa podrškom za dva opsega, UMA-D proširuje pokrivenost. Dostupan je u pojedinačnim i pet pakovanja.

Dimenzije: 201.3 x 128.0 x 32.5 mm

Težina sa nosačem: 480 g

Kućište: spoljna UV plastika

RF konekcije: 2 x RP-SMA

Podržani opseg frekvencija: 2.4 - 2.5 GHz, 5.1 - 5.9 GHz

HPOL Beamwidth: 2.4 GHz 90°, 5 GHz 45°

VPOL Beamwidth: 2.4 GHz 90°, 5 GHz 45°

Elevation Beamwidth: 2.4 GHz 90°, 5 GHz 45°

Maksimum VSWR: 2.5:1

Polarizacija: Dual-Linear

Cross-Pol Izolacija: 2.4 GHz 25 dB, 5 GHz 30 dB

Antenna Gain: 2.4 GHz 10 dBi, 5 GHz 15 dBi

Montiranje: Zid/stub

Kontakt

RUT240

7363

RUT240

RUT240 industrijski LTE WiFi Ruter
4G/LTE ruter za profesionalnu primenu

235,20

196,00

AC12G

7638

AC12G

WiFi frekvencija: Dual Band

WiFi brzina: 400 Mbps at 2.4GHz, 867 Mbps at 5 GHz

Izuzetno brze veze za žičane uređaje(konzole za igre, računare, pametne televizore...)

Vrsta antene: Eksterna

Broj antena: 4 x 5dBi omni directional antennas

Broj LAN Portova:

1x Gigabit WAN Port

3x Gigabit LAN Ports

Napajanje: 12V/1A

Dimenzije: 222mm x 140mm x 32mm

Radna temperatura: 0°C ~ 40°C

45,00

37,50

MP500 KIT AV1000

7226

MP500 KIT AV1000

Komplet **MP500** prenosi mrežne podatke preko postojećih električnih kola,

izbegavajući bilo kakav negativan uticaj prepreka na mrežu

Uživajte u stabilnoj proširenoj mreži sa udaljenošću prenosa do 300 metara (na istom električnom kolu)

Zaštita: Powerline Security: 128-bit AES

Tasteri: Pair/Reset

Standardi i Protokoli:

HomePlug AV2, HomePlug AV, IEEE 1901, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab

Plug & Play

Lako proširenje

Operativna temperatura: 0 ~ 40 °C

Operativna vlažnost: 10 ~ 90%

Dimenzije: 101 x 60 x 36 mm

52,80

44,00