















| NAZIV ARTIKLA | Kat.br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (račun bez PDV) |
|--|---------|---|--------------------------|-----------------------------|
| <p>DS-2TD2617B-6/PA</p> <p style="text-align: center;">DeepinView^{series}</p>  <div style="display: flex; justify-content: space-around; margin-top: 10px;">       </div> | 6370 | <p>KAMERA ZA MERENJE TEMPERATURE TELA</p> <p>U stanju je da otkrije i prati ljude sa višom telesnom temperaturom među prepunom javnom površinom. Može se koristiti na mestima kao što su carina, aerodromi, škole, autobuska stajališta, zdravstveni centri i druge državne i javne institucije.</p> <p>Čip: Vanadium Oxide Uncooled Focal Plane Arrays (termalni), 1/2.7" Progressive Scan CMOS (opticki) Rezolucija: 160 × 120 (izlazna rezolucija slike 320 × 240), optički modul 2688 × 1520 Osetljivost: Color: 0.0089 Lux @(F1.6, AGC ON), B/W: 0.0018 Lux @(F1.6, AGC ON) Širina područja: 8~14μm Objektiv: termalni 6,2mm, optički 8mm IC osvetljenje: Smart diode dometa do 40 metara, IR cut filter (automatski intezitet i ugao) Video kompresija: H.265/H.264/MJPEG Protokoli: IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE Interfejs: Alarmni ulazi/izlazi 2/2, Audio ulazi/izlazi 1/1, reset dugme, 1x RJ45, RS-485, slot za SD karticu do 128GB Alarmne akcije: SD snimanje, relejni izlaz, pametno snimanje, FTP upload, veza e-pošte, audio alarm, beli svetlosni alarm Podešavanje slike: AGC, 3D DNR, WDR 120dB Funkcija slike: Kombinuje detalje termicke i opticke slike (PIP), pokazuje termicku sliku na optickoj Smart funkcije: 3 tipa merenja temperature, 21 pravilo (10 tacaka, 10 oblasti, 1 linija) Merenje temperature odstojanje: sa udaljenosti 1.5-3m Merenje temperature: 30°C do 45°C, sa odstupanjem do maksimalno ±0.5° Jezik menija: Srpski, Engleski i jos 30 jezika Napajanje i potrošnja: 12 VDC - max. 7.5 W, PoE - max 8 W Radna temperatura i nivo zaštite: 10 °C do 35 °C, IP66, TVS 6000V, zaštita od prenapona, zaštita od prolaznih napona Dimenzije i težina: 358,3 x 113,5 x 115,2 mm, Težina 1,76kg</p> | 8.556,00 | 7.130,00 |

| | | | | |
|--|------|--|-----------|-----------|
| <p>DS-2TD2637B-10/P</p> <p style="text-align: center;">DeepinView^{series}</p>  <div style="display: flex; justify-content: space-around; margin-top: 10px;">       </div> | 6371 | <p>KAMERA ZA MERENJE TEMPERATURE TELA</p> <p>U stanju je da otkrije i prati ljude sa višom telesnom temperaturom među prepunom javnom površinom. Može se koristiti na mestima kao što su carina, aerodromi, škole, autobuska stajališta, zdravstveni centri i druge državne i javne institucije.</p> <p>Čip: Vanadium Oxide Uncooled Focal Plane Arrays (termalni), 1/2.7" Progressive Scan CMOS (opticki) Rezolucija: termalni modul 384 × 288, optički modul 2688 × 1520 Osetljivost: Color: 0.0089 Lux @(F1.6, AGC ON), B/W: 0.0018 Lux @(F1.6, AGC ON) Širina područja: 8~14μm Objektiv: termalni 9,7mm, optički 4mm IC osvetljenje: Smart diode dometa do 50 metara, IR cut filter (automatski intezitet i ugao) Video kompresija: H.265/H.264/MJPEG Protokoli: IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE Interfejs: Alarmni ulazi/izlazi 2/2, Audio ulazi/izlazi 1/1, reset dugme, 1x RJ45, RS-485, slot za SD karticu do 256GB Alarmne akcije: SD snimanje, relejni izlaz, pametno snimanje, FTP upload, veza e-pošte Podešavanje slike: AGC, 3D DNR, WDR 120dB Funkcija slike: Kombinuje detalje termicke i opticke slike (PIP), pokazuje termicku sliku na optickoj Smart funkcije: 3 tipa merenja temperature, 21 pravilo (10 tacaka, 10 oblasti, 1 linija) Merenje temperature odstojanje: sa udaljenosti 3-7m Merenje temperature: 30°C do 45°C, sa odstupanjem do maksimalno ±0.5° Jezik menija: Srpski, Engleski i jos 30 jezika Napajanje i potrošnja: 24 VAC - max 9 W, 12 VDC - max. 9 W, PoE - max 9,5 W Radna temperatura i nivo zaštite: 10 °C do 35 °C, IP66, TVS 6000V, zaštita od prenapona, zaštita od prolaznih napona Dimenzije i težina: 376,1 x 119,1 x 118,1 mm, Težina 1,82kg</p> | 13.851,60 | 11.543,00 |
|--|------|--|-----------|-----------|

