

Važi od: 30.08.2026.

ANTENALL d.o.o

Ljiljane Krstić 24, Zemun – Altina

Tel. +381 11 6 356 356

www.antenall.rs

office@antenall.rs

CENOVNIK

Oprema za video nadzor HiLook serija



HiLook

DVR

NAZIV ARTIKLA	Kat. br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (racun bez PDV)
<u>DVR-104G-K1</u>  	10405	DVR-104G-K1 4-ch 2MP Lite Mini 1U H.265 DVR Rezolucija snimanja - 1080p stream: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF@25 fps - 720p stream: 720p/WD1/4CIF/VGA/CIF@ 25fps - SD stream: WD1/4CIF/VGA/CIF@25 fps - Sub-stream: 4CIF@15fps; CIF/QVGA@25 fps IP kamere - 1 kanal do 2 MP rezolucije; ukupno do 5-kanala (bez analognih ulaza) Video i audio - Video kompresija: H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Video izlazi: HDMI i VGA (istovremeni izlaz), - Audio ulazi/izlazi: 1 kanal, RCA + 4-ch preko coax kabla/1× RCA - Dvosmerni audio: 1 kanal, RCA (koristi prvi audio ulaz) Pametne funkcije - Motion Detection 2.0 (do 4 analognih kanala, prepoznavanje čovek/vozilo) - Pametna reprodukcija i pretraga po objektu ili događaju Pomoćni interfejs - 1, RJ45 10M/100M/1000M self-adaptive mrežni interfejs, USB: 2× USB 2.0 (zadnja strana), Alarm ulaz/izlaz: 0/0 Opšte karakteristike - 1× SATA HDD, do 4TB po disku - Napajanje: 12 VDC, 1.5 A - Potrošnja: ≤ 16 W (bez HDD-a) - Dimenzije (DxVxŠ): 200 × 200 × 48 mm - Težina: ≤ 0.8 kg	60,00	50,00
<u>DVR-108G-M1/T</u>  	10402	DVR-108G-M1/T 8-ch 2MP Lite Mini 1U H.265 DVR Rezolucija snimanja - 1080p stream: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF@15 fps - 720p stream: 720p/WD1/4CIF/VGA/CIF@ 15fps - SD stream: WD1/4CIF/VGA/CIF@25 fps - Sub-stream: 4CIF@15fps; CIF/QVGA@25 fps IP kamere - 2 kanal do 2 MP rezolucije; ukupno do 10-kanala (bez analognih ulaza) Video i audio - Video kompresija: H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Video izlazi: HDMI i VGA (istovremeni izlaz), - Audio ulazi/izlazi: 1 kanal, RCA + 8-ch preko coax kabla/1× RCA - Dvosmerni audio: 1 kanal, RCA (koristi prvi audio ulaz) Pametne funkcije - Motion Detection 2.0 (do 8 analognih kanala, prepoznavanje čovek/vozilo) - Pametna reprodukcija i pretraga po objektu ili događaju Pomoćni interfejs - 1, RJ45 10M/100M/1000M self-adaptive mrežni interfejs, USB: 2× USB 2.0(zadnja strana), Alarm ulaz/izlaz: 0/0 Opšte karakteristike - 1× SATA HDD, do 4TB po disku - Napajanje: 12 VDC, 1.5 A - Potrošnja: ≤ 10 W (bez HDD-a) - Dimenzije (DxVxŠ): 200 × 200 × 48 mm - Težina: ≤ 1 kg	81,60	68,00

DVR-216Q-M1  HiLook	8794 DVR-216Q-M1 16-KANALNI Turbo HD SNIMAČ, Motion Detection 2.0 Rezolucija snimanja: Kada je režim 1080p Lite nedostupan: 4 MP lite/1080p/720p/VGA/WD1/4CIF/CIF Kada je režim 1080p Lite dostupan: 4 MP lite/3 MP/1080p lite/720p lite/VGA/WD1/4CIF/CIF Rezolucija snimanja IP kamera: do 6MP, 2-ch ili svih 18 kanala, Enhanced IP mod: 8-ch, ili svih 24 kanala Video kompresija: H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 Audio ulazi/izlazi: 1-ch, RCA, 16-ch preko coaxial Video izlazi: HDMI/VGA istovremeni izlaz HDMI: 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz VGA: 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz Alarmni ulaz/izlaz: 0/0 Pametne funkcije: Motion Detection 2.0 prepoznavanje čoveka/vozila, detekcija lica, detekcija pokreta Dodatni ulazi: 1, RJ45 10M/100M/1000M self-adaptive Ethernet interface, 2 × USB 2.0 zadnja strana Mrežni protokoli: TCP/IP, PPPoE, DHCP, HiLookVision, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF Hard disk: 1 sata HDD maksimalnog kapaciteta 10TB kapaciteta. Opšte: Napajanje 12 VDC, 1.9 A , Potrošnja ≤ 20 W (bez HDD) Radna temperatura: -10 °C to +55 °C Dimezije (DxŠxV): 265 × 225 × 48 mm Težina: ≤ 1.2 kg (bez hard diska)	240,00	200,00
DVR-216U-M2  HiLook	8797 DVR-216U-M2 16-KANALNI Turbo HD SNIMAČ, Motion Detection 2.0 Rezolucija snimanja: 8 MP/5 MP/3K/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF Rezolucija snimanja IP kamera: do 6MP, 8-ch ili svih 24 kanala, Enhanced IP mod: 16-ch, ili svih 32 kanala Video kompresija: H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 Audio ulazi/izlazi: 1-ch, RCA, 16-ch preko coaxial Video izlazi: HDMI/VGA istovremeni izlaz HDMI: 1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz VGA: 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz Alarmni ulaz/izlaz: 0/0 Pametne funkcije: Motion Detection 2.0 prepoznavanje čoveka/vozila, detekcija lica, detekcija pokreta Dodatni ulazi: 11, RJ45 10/100/1000 Mbps self-adaptive Ethernet interface, 1 × USB 2.0 prednja strana, 1 × USB 3.0 zadnja strana Mrežni protokoli: TCP/IP, PPPoE, DHCP, HiLookVision, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF Hard disk: 2 sata HDD maksimalnog kapaciteta 10TB kapaciteta po disku. Opšte: Napajanje 12V DC, 5A, Potrošnja ≤ 25 W (bez HDD) Radna temperatura: -10 °C to +55 °C Dimezije (DxŠxV): 380 × 320 × 48 mm Težina: ≤ 2 kg (bez hard diska)	487,20	406,00

TURBO HD KAMERE

NAZIV ARTIKLA	Kat. br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (racun bez PDV)
<u>THC-B120-P 2.8 mm</u>  	10390	THC-B120-P 2.8 mm 2 MP Fixed Mini Bullet Kamera Rezolucija snimanja: 1920 x 1080 @25fps Senzor slike: 2 MP CMOS Osetljivost: 0.01 Lux@(F2.0, AGC ON), 0 Lux with IR FOV (Polje vidljivosti): horizontalno 103° Unapređenje slike: WDR, BLC, HLC, 3D DNR Osvetljenje: IR 30m Video izlaz: 4 u 1 (TVI/AHD/CVI/CVBS) PIR detektor: domet do 20 m Ostale karakteristike: DWDR, BLC Napajanje i potrošnja: 12 VDC ± 25%, max. 4 W Radna temperatura: -40°C to 60°C Zaštita: IP66 Dimenzije: 165 mm × 62 mm × 58 mm Materijal: Plastika Težina: 150 g Kompatibilni pribor: HIA-J101	24,00	20,00
<u>THC-T120-P 2.8 mm</u>  	10391	THC-T120-P 2.8 mm 2 MP Fixed Mini Turret Kamera Rezolucija snimanja: 1920 x 1080 @25fps Senzor slike: 2 MP CMOS Osetljivost: 0.01 Lux@(F2.0, AGC ON), 0 Lux with IR FOV (Polje vidljivosti): horizontalno 103° Unapređenje slike: WDR, BLC, HLC, 3D DNR Osvetljenje: IR 20m Video izlaz: 4 u 1 (TVI/AHD/CVI/CVBS) PIR detektor: domet do 20 m Ostale karakteristike: DWDR, BLC Napajanje i potrošnja: 12 VDC ± 25%, max. 4 W Radna temperatura: -40°C to 60°C Zaštita: IP66 Dimenzije: Ø 85.4 mm × 76.12 mm Materijal: Plastika Težina: 130 g Kompatibilni pribor: HIA-J101, HIA-B201, HIA-B301, HIA-B401-110T	25,20	21,00

NVR

NAZIV ARTIKLA	Kat. br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (racun bez PDV)
NVR-104H-D  	10403	NVR-104H-D 4-ch do 6MP Mini 1U 4 NVR Rezolucija snimanja - 6 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF Kapacitet dekodiranja: - 4-ch@1080p (30 fps) or 2-ch@4 MP (30 fps) or 1-ch@6 MP (30 fps) Video i audio - Ulazno/Izlazno Bandwidth: 40/60Mbps - Video kompresija: H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Video izlazi: HDMI i VGA (istovremeni izlaz), - Audio ulazi/izlazi: 0/0 - Dvosmerni audio: 0 Pametne funkcije - Podržava detekciju prelaska linije i upada u zonu - Pametna pretraga odabranog područja na video snimku i pametna reprodukcija radi veće efikasnosti pregleda - Automatsko pretraživanje i dodavanje mrežnih kamera nakon aktivacije uređaja Pomoćni interfejs - 1, RJ45 10M/100M/1000M self-adaptive mrežni interfejs, USB: 2× USB 2.0 (zadnja strana), Alarm ulaz/izlaz: 0/0 Opšte karakteristike - 1× SATA HDD, do 6TB po disku - Napajanje: 12 VDC, 1.5 A - Potrošnja: ≤ 10 W (bez HDD-a) - Dimenzije (DxVxŠ): 200 × 200 × 48 mm - Težina: ≤ 1 kg	84,00	70,00
NVR-108H-D  	10404	NVR-108H-D 8-ch do 6MP Mini 1U 4 NVR Rezolucija snimanja - 6 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF Kapacitet dekodiranja: - 4-ch@1080p (30 fps) or 2-ch@4 MP (30 fps) or 1-ch@6 MP (30 fps) Video i audio - Ulazno/Izlazno Bandwidth: 60/60Mbps - Video kompresija: H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Video izlazi: HDMI i VGA (istovremeni izlaz), - Audio ulazi/izlazi: 0/0 - Dvosmerni audio: 0 Pametne funkcije - Podržava detekciju prelaska linije i upada u zonu - Pametna pretraga odabranog područja na video snimku i pametna reprodukcija radi veće efikasnosti pregleda - Automatsko pretraživanje i dodavanje mrežnih kamera nakon aktivacije uređaja Pomoćni interfejs - 1, RJ45 10M/100M/1000M self-adaptive mrežni interfejs, USB: 2× USB 2.0 (zadnja strana), Alarm ulaz/izlaz: 0/0 Opšte karakteristike - 1× SATA HDD, do 6TB po disku - Napajanje: 12 VDC, 1.5 A - Potrošnja: ≤ 10 W (bez HDD-a) - Dimenzije (DxVxŠ): 200 × 200 × 48 mm - Težina: ≤ 1 kg	106,80	89,00

IP KAMERE

NAZIV ARTIKLA	Kat. br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (racun bez PDV)
<u>IPC-D620HA-LZU 2.8-12mm</u>  	8783	IPC-D620HA-LZU 2.8-12mm 2 MP Dual Light MD 2.0 Verifokal Dom Mrežna Kamera Rezolucija snimanja: 1920 × 1080 @30fps Senzor slike: 1/2.9" Progressive Scan CMOS Osetljivost: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR FOV (Polje vidljivosti): horizontalno 102.4° do 31.2°, vertikalno 54.4° do 17.5°, dijagonalno 121.8° to 35.7° Unapređenje slike: D WDR, BLC, HLC, 3D DNR Osvetljenje: Bela svetlost i IR, dometa do 30m Interfejsi: 1 RJ45 10 M/100 M self-adaptive Ethernet port, Integrirani mikrofoni, reset dugme, slot za SD karticu do 512 Gb Protokoli: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, RTCP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP Mrežni standardi: Open Network Video Interface (Profile S, Profile G, Profile T), ISAPI, SDK Događaji: Detekcija pokreta (podrška za alarmiranje putem određenih vrsta ciljeva (čovjek i vozilo)), alarm za ometanje video zapisa, izuzetak Napajanje i potrošnja: 12 VDC ± 25%, 0.8 A, max. 9.6 W; PoE: IEEE 802.3af, Class 3, max. 12 W Radna temperatura: -30°C to 60°C Zaštita: IP67: IEC 60529-2013 Dimenzije: Ø121.5 mm × 97.6 mm Materijal: Metal i plastika Težina: 540 g Kompatibilni pribor: DS-1280ZJ-DM46, DS-2280ZJ-WA120, DS-1272ZJ-120, DS-1272ZJ-120B, DS-1271ZJ-120, DS-2200ZJ-WA-120, DS-2200ZJ-WAJ-120, DS-2210ZJ-WA-120, DS-1275ZJ-SUS, DS-1276ZJ-SUS	180,00	150,00
<u>IPC-B120HA-LUC 2.8 mm</u>  	10392	IPC-B120HA-LUC 2.8 mm 2 MP Smart Hybrid Light Fixed Bullet Mrežna Kamera Rezolucija snimanja: 1920 × 1080 @25fps Senzor slike: 1/2.9" Progressive Scan CMOS Osetljivost: Color: 0.01 Lux @ (F2.2, AGC ON), B/W: 0 Lux with IR FOV (Polje vidljivosti): horizontalno 101°, vertikalno 56°, dijagonalno 118° Unapređenje slike: D WDR, BLC, HLC, 3D DNR Osvetljenje: Belo svetlo / IR: 15m / 20m Interfejsi: 1 RJ45 10 M/100 M self-adaptive Ethernet port, Integrirani mikrofoni Protokoli: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTCP, RTSP, NTP, IGMP, IPv4, IPv6, UDP, QoS Mrežni standardi: Open Network Video Interface (Profile S, Profile T), ISAPI, SDK Događaji: Detekcija pokreta (podrška za alarmiranje putem određenih vrsta ciljeva (čovjek i vozilo)) Napajanje i potrošnja: 12 VDC ± 25%, 0.42 A, max. 5 W; PoE: IEEE 802.3af, Class 3, max. 6.5 W Radna temperatura: -30°C to 60°C Zaštita: IP67: IEC 60529-2013 Dimenzije: 138.8 mm × 60.9 mm × 57.9 mm Materijal: plastika Težina: 175 g Kompatibilni pribor: DS-1275ZJ-SUS, DS-1276ZJ-SUS, DS-1280ZJ-XS	52,80	44,00

<u>IPC-T220HA-LUC 2.8 mm</u>  HiLook	10393 IPC-T220HA-LUC 2.8 mm 2 MP Smart Hybrid Light Fixed Turret Mrežna Kamera Rezolucija snimanja: 1920 × 1080 @25fps Senzor slike: 1/2.9" Progressive Scan CMOS Osetljivost: Color: 0.01 Lux @ (F2.2, AGC ON),B/W: 0 Lux with IR FOV (Polje vidljivosti): horizontalno 101°, vertikalno 56°, dijagonalno 118° Unapređenje slike: D WDR, BLC, HLC, 3D DNR Osvetljenje: Belo svetlo / IR: 15m / 20m Interfejsi: 1 RJ45 10 M/100 M self-adaptive Ethernet port, Integrisani mikrofoni Protokoli: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTCP, RTSP,NTP, IGMP, IPv4, IPv6, UDP, QoS Mrežni standardi: Open Network Video Interface (Profile S, Profile T),ISAPI,SDK Događaji: Detekcija pokreta (podrška za alarmiranje putem određenih vrsta ciljeva (čovjek i vozilo)) Napajanje i potrošnja: 12 VDC ± 25%, 0.42 A, max. 5 W; PoE: IEEE 802.3af, Class 3, max. 6.5 W Radna temperatura: -30°C to 60°C Zaštita: IP67: IEC 60529-2013 Dimenzije: Ø 110 mm × 102.7 mm Materijal: Metal i plastika Težina: 345 g Kompatibilni pribor: DS-1275ZJ-SUS, DS-1276ZJ-SUS, DS-1280ZJ-S, DS-1272ZJ-110-TRS	52,80	44,00
<u>IPC-B140HA-LUC 2.8 mm</u>  HiLook	10394 IPC-B140HA-LUC 2.8 mm 4 MP Smart Hybrid Light Fixed Bullet Mrežna Kamera Rezolucija snimanja: 2560 × 1440 @20fps Senzor slike: 1/2.8" Progressive Scan CMOS Osetljivost: Color: 0.01 Lux @ (F2.2, AGC ON),B/W: 0 Lux with IR FOV (Polje vidljivosti): horizontalno 104°, vertikalno 57°, dijagonalno 123° Unapređenje slike: D WDR, BLC, HLC, 3D DNR Osvetljenje: Belo svetlo / IR: 15m / 20m Interfejsi: 1 RJ45 10 M/100 M self-adaptive Ethernet port, Integrisani mikrofoni Protokoli: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTCP, RTSP,NTP, IGMP, IPv4, IPv6, UDP, QoS Mrežni standardi: Open Network Video Interface (Profile S, Profile T),ISAPI,SDK Događaji: Detekcija pokreta (podrška za alarmiranje putem određenih vrsta ciljeva (čovjek i vozilo)) Napajanje i potrošnja: 12 VDC ± 25%, 0.42 A, max. 5 W; PoE: IEEE 802.3af, Class 3, max. 6.5 W Radna temperatura: -30°C to 60°C Zaštita: IP67: IEC 60529-2013 Dimenzije: 138.8 mm × 60.9 mm × 57.9 mm Materijal: plastika Težina: 250 g Kompatibilni pribor: DS-1275ZJ-SUS, DS-1276ZJ-SUS, DS-1280ZJ-XS	70,80	59,00
<u>IPC-D640HA-LZU 2.8-12mm</u>  HiLook	8784 IPC-D640HA-LZU 2.8-12mm 4 MP Dual Light MD 2.0 Verifokal Dom Mrežna Kamera Rezolucija snimanja: 2560 × 1440 @20fps Senzor slike: 1/3 " Progressive Scan CMOS Osetljivost: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR FOV (Polje vidljivosti): horizontalno 96.7° do 29.7°, vertikalno 51.7° do 16.7°, dijagonalno 114.3° do 34° Unapređenje slike: WDR, BLC, HLC, 3D DNR Osvetljenje: Bela svetlost i IR, dometa do 30m Interfejsi: 1 RJ45 10 M/100 M self-adaptive Ethernet port, Integrisani mikrofoni, reset dugme, slot za SD karticu do 512 Gb Protokoli: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, RTCP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP Mrežni standardi: Open Network Video Interface (Profile S, Profile G, Profile T), ISAPI, SDK Događaji: Detekcija pokreta (podrška za alarmiranje putem određenih vrsta ciljeva (čovjek i vozilo)), alarm za ometanje video zapisa, izuzetak Napajanje i potrošnja: 12 VDC ± 25%, 0.8 A, max. 9.6 W; PoE: IEEE 802.3af, Class 3, max. 12 W Radna temperatura: -30°C to 60°C Zaštita: IP67: IEC 60529-2013 Dimenzije: Ø121.5 mm × 97.6 mm Materijal: Metal i plastika Težina: 540 g Kompatibilni pribor: DS-1280ZJ-DM46, DS-2280ZJ-WA120, DS-1272ZJ-120, DS-1272ZJ-120B, DS-1271ZJ-120, DS-2200ZJ-WA-120, DS-2200ZJ-WAJ-120, DS-2210ZJ-WA-120, DS-1275ZJ-SUS, DS-1276ZJ-SUS	202,80	169,00

IPC-T240HA-LUC 2.8 mm



HiLook

10395

IPC-T240HA-LUC 2.8 mm
4 MP Smart Hybrid Light Fixed Turret Mrežna Kamera

Rezolucija snimanja: 2560 × 1440 @20fps
Senzor slike: 1/2.8" Progressive Scan CMOS
Osetljivost: Color: 0.01 Lux @ (F2.2, AGC ON), B/W: 0 Lux with IR
FOV (Polje vidljivosti): horizontalno 104°, vertikalno 57°, dijagonalno 123°
Unapređenje slike: D WDR, BLC, HLC, 3D DNR
Osvetljenje: Belo svetlo / IR: 15m / 20m
Interfejsi: 1 RJ45 10 M/100 M self-adaptive Ethernet port, Integrirani mikrofoni
Protokoli: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTCP, RTSP, NTP, IGMP, IPv4, IPv6, UDP, QoS
Mrežni standardi: Open Network Video Interface (Profile S, Profile T), ISAPI, SDK
Događaji: Detekcija pokreta (podrška za alarmiranje putem određenih vrsta ciljeva (čovjek i vozilo))
Napajanje i potrošnja: 12 VDC ± 25%, 0.42 A, max. 5 W; PoE: IEEE 802.3af, Class 0, max. 6.5 W
Radna temperatura: -30°C to 60°C
Zaštita: IP67: IEC 60529-2013
Dimenzije: Ø 112 mm × 88.4 mm
Materijal: Metal i plastika
Težina: 345 g

Kompatibilni pribor:
DS-1275ZJ-SUS, DS-1276ZJ-SUS, DS-1280ZJ-S, DS-1272ZJ-110-TR

70,80

59,00