


Važi od: 12.10.2026.

Cenovnik termalnih i digitalnih optičkih nišana



HIKMICRO

TRUST YOUR JOURNEY

ANTENALL DOO

Ljiljane Krstić 24, Zemun-Altina

tel: 011/6356356

office@antenall.rs

ww.antenall.rs

OPTIČKI NIŠAN - DNEVNO/NOĆNI

NAZIV ARTIKLA	Kat. br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (racun bez PDV)
A50E Alpex 4K  	10292	A50E Alpex 4K Digitalni dnevno/noćni nišan namenjen za lov, sa 4K senzorom koji obezbeđuje izuzetno detaljnu sliku i stabilne performanse u uslovima slabog osvetljenja. Ključne karakteristike - 4K CMOS senzor za visok nivo detalja - Podesiva blenda za rad u različitim svetlosnim uslovima - Stabilna slika noću uz IR podršku - Dug rad baterije (do ~11 h) - Robusno kućište otporno na trzaj i vremenske uslove - Interno snimanje + Wi-Fi povezivanje Tehničke specifikacije Senzor i optika: Tip senzora: CMOS Rezolucija: 3840 × 2160 (4K) Veličina piksela: 2.9 μm Objektiv: 50 mm Blenda: F1.2 – F2.5 (podesiva) Prikaz i uvećanje: Osnovno uvećanje: 3.5× Digitalni zoom: do ~28× Vidno polje (FOV): ~8.8° × 5.0° Tip i rezolucija ekrana: OLED, 1920 × 1080 Noćni rad / termalne performanse: Režimi rada: Day / Night / Auto IR kompatibilnost: 850 nm / 940 nm Funkcije: Wi-Fi: da Aplikacija: Hikmicro Sight Snimanje: video / foto / audio Dodatne opcije: različiti nišanski končanici (reticles), zeroing profili Napajanje: Tip baterije: interna + izmenjiva Autonomija: do ~11 h Punjenje: USB-C Mehaničke karakteristike: Zaštita: IP67 Otpornost na trzaj: do ~1000 g / 6000 J Radna temperatura: -30°C do +55°C Montaža: standard 30 mm Dimenzije i masa: Dimenzije: ~442 × 78 × 84 mm Težina: ~1060 g	649,00	540,83

A50EL Alpex 4K



10291

A50EL Alpex 4K
Digitalni dnevno/noćni nišan za lov sa 4K senzorom i integrisanim laserskim daljinomerom (LRF), omogućava precizno određivanje distance i stabilno gađanje na većim daljinama.

Ključne karakteristike
- 4K CMOS senzor za izuzetno detaljnu sliku
- Integrisani laserski daljinomer (LRF) do ~1000 m
- Podesiva blenda za različite svetlosne uslove
- Stabilan noćni rad uz IR podršku
- Dug rad baterije za terensku upotrebu
- Snimanje i Wi-Fi povezivanje

Tehničke specifikacije
Senzor i optika:
Tip senzora: CMOS
Rezolucija: 3840 × 2160 (4K)
Veličina piksela: 2.9 μm
Objektiv: 50 mm
Blenda: F1.2 – F2.5 (podesiva)

Prikaz i uvećanje:
Osnovno uvećanje: 3.5×
Digitalni zoom: do ~28×
Vidno polje (FOV): ~8.8° × 5.0°
Tip i rezolucija ekrana: OLED, 1920 × 1080

Noćni rad / termalne performanse:
Režimi rada: Day / Night / Auto
IR kompatibilnost: 850 nm / 940 nm

Funkcije:
LRF (laserski daljinomer): do ~1000 m
Wi-Fi: da
Aplikacija: Hikmicro Sight
Snimanje: video / foto / audio
Dodatne opcije: balistički kalkulator, više nišanskih profila (zeroing), reticles

Napajanje:
Tip baterije: interna + izmenjiva
Autonomija: do ~11 h
Punjenje: USB-C

Mehaničke karakteristike:
Zaštita: IP67
Otpornost na trzaj: do ~1000 g / 6000 J
Radna temperatura: -30°C do +55°C
Montaža: standard 30 mm

Dimenzije i masa:
Dimenzije: ~442 × 84 × 92 mm
Težina: ~1150 g

849,00

707,50

A50PL Alpex  	10298	A50PL Alpex Digitalni dnevno/noćni nišan za lov iz PRO serije sa 12MP senzorom i integrisanim laserskim daljinomerom (LRF), namenjen za precizno osmatranje i gađanje uz pouzdano određivanje distance u svim svetlosnim uslovima. Ključne karakteristike 12MP CMOS senzor (4.5K klasa – 4512×2512) Integrisani LRF do ~1200 m (±1 m preciznost) Light Pro algoritam za vrhunsku sliku u slabom svetlu 50 mm F1.8 objektiv (širok FOV za pregled terena) AMOLED ekran 1920×1080 visoke jasnoće 4×–24× uvećanje (kontinuirani zoom) Lakša PRO konstrukcija (~850–890 g) Snimanje + Wi-Fi + balističke funkcije Tehničke specifikacije Senzor i optika: Tip senzora: CMOS Rezolucija: 4512 × 2512 (12 MP) Objektiv: 50 mm Blenda: F1.8 Minimalna distanca fokusa: ~3 m Prikaz i uvećanje: Osnovno uvećanje: 4× Digitalni zoom: do ~24× Vidno polje (FOV): ~12.6 m / 100 m Ekran: AMOLED 0.6", 1920 × 1080 Noćni rad / režimi: Režimi: Day / Night / Auto Palete: B/W, zeleno, žuto Light Pro poboljšanje slike Funkcije: LRF (laserski daljinomer): do ~1200 m, ±1 m Balistički kalkulator Wi-Fi: da Snimanje: video / foto / audio Recoil-activated recording Interna memorija: 64 GB Napajanje: Tip baterije: interna + 18650 Autonomija: do ~7 h Punjenje: USB-C Mehaničke karakteristike: Zaštita: IP67 Otpornost na trzaj: do ~6000 J (klasa) Montaža: 30 mm tubus Radna temperatura: -30°C do +55°C Dimenzije i masa: Težina: ~850–890 g <td data-bbox="1260 15 1418 1227"> 999,00 </td> <td data-bbox="1418 15 1572 1227"> 832,50 </td>	999,00	832,50
---	---	--	--	--

A50P Alpex Pro



10297

A50P Alpex Pro
Digitalni dnevno/noćni nišan za lov, zasnovan na 12MP senzoru i PRO platformi, namenjen za visoku jasnoću slike u svim svetlosnim uslovima bez integrisanog daljinomera.

Ključne karakteristike
12MP CMOS senzor (viša rezolucija od 4K klase)
Light Pro algoritam za bolji kontrast u slabom svetlu
Stabilna slika u dnevnim i noćnim uslovima
4–24× uvećanje sa glatkim digitalnim zoom-om
Lakša konstrukcija u odnosu na A50E
Snimanje + Wi-Fi povezivanje
Tehničke specifikacije

Senzor i optika:
Tip senzora: CMOS
Rezolucija: 4512 × 2512 (12MP)
Objektiv: 50 mm
Blenda: F1.8
Minimalno fokusiranje: ~3 m

Prikaz i uvećanje:
Osnovno uvećanje: 4×
Digitalni zoom: do ~24×
Vidno polje (FOV): ~12.6 m / 100 m
Ekran: 0.6” AMOLED, 1920 × 1080

Noćni rad / režimi:
Day / Night / Auto režimi
Palete prikaza (B/W, zeleno, žuto)
Light Pro poboljšanje slike pri slabom svetlu

Funkcije:
Wi-Fi: da
Aplikacija: Hikmicro Sight
Snimanje: video / foto / audio
Recoil aktivacija snimanja (HIKMICRO funkcija)
64 GB interna memorija

Napajanje:
Baterija: kombinacija interne + 18650
Autonomija: do ~7 h
Punjenje: USB-C

Mehaničke karakteristike:
Zaštita: IP67
Otpornost na trzaj: do ~6000 J
Radna temperatura: -30°C do +55°C
Montaža: 30 mm tubus

Dimenzije i masa:
Težina: ~850–900 g

849,00

707,50

OPTIČKI NIŠAN -TERMALNI

NAZIV ARTIKLA	Kat. br.	Karakteristike	CENA EUR (gotovinski)	CENA EUR (racun bez PDV)
SH35 3.0 Stellar 3.0  	10287	SH35 3.0 Stellar 3.0 Termalni nišan za lov zasnovan na VOx 384×288 senzoru, sa 35 mm optikom i visokom termalnom osetljivošću, namenjen za detekciju i precizno gađanje na velikim daljinama u potpunom mraku i otežanim uslovima. Ključne karakteristike VOx 384×288 @ 12 μm termalni senzor NETD < 15 mK (visoka osetljivost slike) Detekcija do ~1800 m 35 mm F1.0 objektiv OLED 2560×2560 ekran visoke rezolucije Kontinuirani digitalni zoom do ~24× IP67 zaštita (voda, prašina, ekstremni uslovi) Do ~9 h autonomije (kombinovana baterija) Tehničke specifikacije Termalni modul: Tip senzora: VOx uncooled FPA Rezolucija: 384 × 288 Pixel pitch: 12 μm Spektralni opseg: 8–14 μm NETD: < 15 mK @25°C Frame rate: 50 Hz Optika: Objektiv: 35 mm Blenda: F1.0 Fokus: ručni (focus ring) Domet detekcije: do ~1800 m Prikaz i uvećanje: Osnovno uvećanje: ~4.2× Digitalni zoom: do ~24.2× Vidno polje: ~7.5° × 5.7° Ekran: OLED 2560 × 2560 (1.03") Funkcije: Palette prikaza: Black Hot, White Hot, Red Hot, Fusion, itd. PiP (picture-in-picture) Hot track (praćenje toplog objekta) Wi-Fi hotspot + mobilna aplikacija Video / foto / audio snimanje Recoil-activated recording Zeroing profili (do 5) Balistički kalkulator (zavisi od verzije tržišta) Memorija: Interna memorija: 64 GB (eMMC) Napajanje: Kombinacija: interne baterije + 18650 eksterni akumulator Autonomija: do ~9 h Punjenje: USB-C (QC3.0 podrška) Mehaničke karakteristike: Zaštita: IP67 Otpornost na trzaj: do ~1000 g / 0.4 ms Montaža: 30 mm tubus Radna temperatura: -30°C do +55°C Dimenzije i masa: Dimenzije: ~410 × 85 × 69.4 mm Težina: ~800 g (bez spoljne baterije)	1999,00	1665,83

SH35L 3.0 Stellar  	10288	SH35L 3.0 Stellar Termalni nišan za lov sa integrisanim laserskim daljinomerom (LRF), zasnovan na 384×288 senzoru visoke osetljivosti, namenjen za precizno gađanje na većim daljinama u potpunom mraku. Ključne karakteristike VOx 384×288 @12 μm senzor (NETD <15 mK) Integrisani laserski daljinomer do ~1000 m 35 mm F1.0 objektiv (detekcija do ~1800 m) OLED ekran 2560×2560 visoke rezolucije HSIS (shutterless) + Image Pro obrada slike Do ~9 h rada (interna + 18650 baterija) Robusno kućište (IP67, otpornost na trzaj) Tehničke specifikacije Termalni modul: Tip senzora: VOx uncooled FPA Rezolucija: 384 × 288 Pixel pitch: 12 μm Spektralni opseg: 8–14 μm NETD: < 15 mK @25°C Frame rate: 50 Hz Optika: Objektiv: 35 mm Blenda: F1.0 Fokus: ručni (focus ring) Domet detekcije: do ~1800 m Prikaz i uvećanje: Osnovno uvećanje: 4.2× Digitalni zoom: do ~24.2× Vidno polje (FOV): ~7.5° × 5.7° Ekran: OLED, 2560 × 2560 (1.03") Noćni rad / termalne performanse: Palette: Black Hot, White Hot, Red Hot, Fusion, Green/Red Mono HSIS (shutterless sistem) Image Pro obrada slike Funkcije: LRF (laserski daljinomer): do ~1000 m, ±1 m Wi-Fi: da Snimanje: video / foto / audio Recoil-activated recording PiP (picture-in-picture) Hot Track Zeroing profili: do 5 Balistički kalkulator Memorija: Interna memorija: 64 GB (eMMC) Napajanje: Tip baterije: 2× interna + 1× 18650 (eksterna) Autonomija: do ~9 h Punjenje: USB-C (QC3.0) Mehaničke karakteristike: Zaštita: IP67 Otpornost na trzaj: ~1000 g / 0.4 ms Radna temperatura: -30°C do +55°C Montaža: 30 mm Dimenzije i masa: Dimenzije: ~410 × 85 × 86.3 mm Težina: ~830 g (bez spoljne baterije)	2299,00	1915,83
---	---	---	---	---

SQ35L 3.0 Stellar



10296

SQ35L 3.0 Stellar

Termalni nišan za lov sa 640×512 senzorom i integrisanim laserskim daljinomerom (LRF), namenjen za maksimalnu jasnoću slike i precizno određivanje distance u svim uslovima vidljivosti.

Ključne karakteristike

640×512 @12 μm termalni senzor (značajno više detalja u odnosu na 384 seriju)
NETD <15 mK – visoka osetljivost i kontrast slike
Integrisani LRF do ~1000 m
35 mm F1.0 objektiv (detekcija do ~1800 m)
Široko vidno polje (prednost u lovu na srednjim distancama)
OLED ekran 2560×2560 visoke rezolucije
HSIS (shutterless) + Image Pro obrada slike
Do ~9 h rada (interna + 18650 baterija)

Tehničke specifikacije

Termalni modul:

Tip senzora: VOx uncooled FPA
Rezolucija: 640 × 512
Pixel pitch: 12 μm
Spektralni opseg: 8–14 μm
NETD: < 15 mK @25°C
Frame rate: 50 Hz

Optika:

Objektiv: 35 mm
Blenda: F1.0
Fokus: ručni (focus ring)
Domet detekcije: do ~1800 m

Prikaz i uvećanje:

Osnovno uvećanje: 2.5×
Digitalni zoom: do ~24.5×
Vidno polje (FOV): ~12.5° × 10.0° (≈21.9 m / 100 m)
Ekran: OLED, 2560 × 2560 (1.03")

Noćni rad / termalne performanse:

Paleta: Black Hot, White Hot, Red Hot, Fusion, Green/Red Mono
HSIS (shutterless sistem)
Image Pro obrada slike

Funkcije:

LRF (laserski daljinomer): do ~1000 m, ±1 m
Wi-Fi: da
Snimanje: video / foto / audio
Recoil-activated recording
PiP (picture-in-picture)
Hot Track
Zeroing profili: do 5
Balistički kalkulator

Memorija:

Interna memorija: 64 GB (eMMC)

Napajanje:

Tip baterije: 2× interna + 1× 18650
Autonomija: do ~9 h
Punjenje: USB-C (QC3.0)

Mehaničke karakteristike:

Zaštita: IP67
Otpornost na trzaj: ~1000 g / 0.4 ms
Radna temperatura: -30°C do +55°C
Montaža: 30 mm

Dimenzije i masa:

Dimenzije: ~410 × 85 × 86.3 mm
Težina: ~830 g (bez spoljne baterije)

2699,00

2249,17

SQ50L 3.0 Stellar



10289

SQ50L 3.0 Stellar
Termalni nišan za lov sa 640×512 senzorom i 50 mm optikom, opremljen integrisanim laserskim daljinomerom (LRF), namenjen za maksimalnu preciznost i rad na velikim daljinama u potpunom mraku.

Ključne karakteristike
640×512 @12 μm termalni senzor (premium klasa detalja)
NETD <15 mK – vrhunska osetljivost i kontrast
50 mm objektiv (detekcija do ~2600 m)
Integrisani LRF do ~1000 m (±1 m preciznost)
OLED ekran 2560×2560 visoke rezolucije
Image Pro 3.0 + HSIS (shutterless rad bez “zamrzavanja”)
Dug rad (~9 h, interna + 18650 baterija)
Fino podešavanje (1.3 cm @100 m klik)
Tehničke specifikacije

Termalni modul:
Tip senzora: VOx uncooled FPA
Rezolucija: 640 × 512
Pixel pitch: 12 μm
Spektralni opseg: 8–14 μm
NETD: < 15 mK @25°C
Frame rate: 50 Hz

Optika:
Objektiv: 50 mm
Blenda: F1.0
Fokus: ručni (focus ring)
Domet detekcije: do ~2600 m

Prikaz i uvećanje:
Osnovno uvećanje: 3.6×
Digitalni zoom: do ~26.6× (kontinuirani)
Vidno polje (FOV): ~8.8° × 7.0° (≈15.4 × 12.3 m / 100 m)
Ekran: OLED, 2560 × 2560 (1.03”)

Noćni rad / termalne performanse:
Paleta: Black Hot, White Hot, Red Hot, Fusion, Green/Red Mono
HSIS (shutterless sistem)
Image Pro 3.0 obrada slike

Funkcije:
LRF (laserski daljinomer): do ~1000 m, ±1 m
Balistički kalkulator
Wi-Fi: da
Snimanje: video / foto / audio
Recoil-activated recording
PiP (picture-in-picture)
Hot Track
Zeroing profili: do 5
Memorija:
Interna memorija: 64 GB (eMMC)

Napajanje:
Tip baterije: 2× interna + 1× 18650 (eksterna)
Autonomija: do ~9 h
Punjenje: USB-C (QC3.0)

Mehaničke karakteristike:
Zaštita: IP67
Otpornost na trzaj: ~1000 g / 0.4 ms
Radna temperatura: -30°C do +55°C
Montaža: 30 mm

Dimenzije i masa:
Dimenzije: ~422.5 × 88.4 × 74.5 mm
Težina: ~860 g (bez spoljne baterije)

3799,00

3165,83

SX60LS 3.0 Stellar



10290

SX60LS 3.0 Stellar
Termalni nišan za lov najviše klase sa 1280×1024 senzorom i integrisanim laserskim daljinomerom, namenjen za maksimalnu preciznost i detekciju na ekstremnim daljinama.

Ključne karakteristike
1280×1024 @12 μm termalni senzor (flagship nivo detalja)
NETD ≤15 mK – vrhunska osetljivost u svim uslovima
60 mm objektiv (detekcija do ~3100 m)
Integrisani LRF do ~1000 m (±1 m)
OLED ekran 2560×2560 visoke rezolucije
Image Pro 3.0 + Sync Pro (smanjen lag slike)
Balistički kalkulator za precizno gađanje
Robusna konstrukcija (IP67, otpornost na trzaj)

Tehničke specifikacije
Termalni modul:
Tip senzora: VOx uncooled FPA
Rezolucija: 1280 × 1024
Pixel pitch: 12 μm
Spektralni opseg: 8–14 μm
NETD: ≤ 15 mK
Frame rate: 50 Hz

Optika:
Objektiv: 60 mm
Blenda: F1.0
Fokus: ručni (focus ring)
Domet detekcije: do ~3100 m

Prikaz i uvećanje:
Osnovno uvećanje: 2.5×
Digitalni zoom: do ~28.5× (kontinuirani)
Vidno polje (FOV): ~14.6° × 11.7° (≈25.6 × 20.5 m / 100 m)
Ekran: OLED, 2560 × 2560 (1.03")

Noćni rad / termalne performanse:
Paleta: Black Hot, White Hot, Red Hot, Fusion, Green/Red Mono
Image Pro 3.0 obrada slike
Sync Pro (smanjenje kašnjenja slike do ~60%)

Funkcije:
LRF (laserski daljinomer): do ~1000 m, ±1 m
Balistički kalkulator: da
Wi-Fi: da
Snimanje: video / foto / audio
Recoil-activated recording
PiP (picture-in-picture)
Zeroing profili: do 5

Memorija:
Interna memorija: 64 GB

Napajanje:
Tip baterije: 2× interna + 1× 18650
Autonomija: ~6.5 – 9 h (zavisno od režima)
Punjenje: USB-C (QC3.0)

Mehaničke karakteristike:
Zaštita: IP67
Otpornost na trzaj: ~1000 g / 0.4 ms
Radna temperatura: -30°C do +55°C
Montaža: 30 mm

Dimenzije i masa:
Dimenzije: ~453 × 94 × 79 mm
Težina: ~1150 g

5799,00

4832,50

NH35L Neos	10448	NH35L Neos HIKMICRO NEOS NH35L termalni nišan opremljen je termalnim detektorom rezolucije 384 × 288 piksela sa veličinom piksela od 12 μm i NETD vrednošću manjom od 18 mK, što omogućava izuzetnu osetljivost i precizno uočavanje temperaturnih razlika. Napredni algoritam za obradu slike Image Pro 3.0, sistem bez zatvarača (HSIS – Shutterless Image System) i Sync Pro algoritam obezbeđuju gladak i detaljan prikaz slike uz minimalno kašnjenje. Zahvaljujući velikom 0,49" AMOLED ekranu, model NH35L pruža izuzetno kvalitetan i impresivan prikaz, čime se povećava udobnost i efikasnost tokom korišćenja. Prikaz slike: Ekran: 0.49 inča AMOLED Palete boja: Crna, Bela, Crvena, Fuzija, Zelena Image Pro 3.0 + Sync Pro (smanjen lag slike) Termalni modul: Tip senzora: VOx uncooled FPA Rezolucija: 384 × 288 Pixel pitch: 12 μm Spektralni opseg: 8–14 μm NETD: ≤ 18 mK Frame rate: 50 Hz Optika: Objektiv: 35 mm Blenda: F1.0 Fokus: ručni (focus ring) Domet detekcije: do ~1800 m Prikaz i uvećanje: Osnovno uvećanje: 3.2× Digitalni zoom: do ~25.6× (kontinuirani) Vidno polje (FOV): 7.6° x 5.7° / 13.1 m x 10.0 m Funkcije: LRF (laserski daljinomer): do ~1000 m, ±1 m Balistički kalkulator: da Wi-Fi: da Snimanje: video / foto / audio Recoil-activated recording PiP (picture-in-picture) Zeroing profili: do 5 Memorija: Interna memorija: 64 GB Napajanje: Tip baterije: 1× interna + 1× 18650 eksterna Autonomija: ~ 8 h (zavisno od režima) Punjenje: USB-C (QC3.0) Mehaničke karakteristike: Zaštita: IP67 Otpornost na trzaj: ~1000 g / 0.4 ms Radna temperatura: -30°C do +55°C Montaža: 30 mm Dimenzije i masa: Dimenzije: ~345.6 × 86 × 75.8 mm Težina: ~570 g	1659,00	1382,50
--	---	--	---	---

NE25 Neos   HIKMICRO	10449	NE25 Neos HIKMICRO NEOS NE25 termalni nišan opremljen je termalnim detektorom rezolucije 256 × 192 piksela sa NETD vrednošću manjom od 18 mK, što omogućava izuzetnu osetljivost i jasno uočavanje temperaturnih razlika. Napredni algoritam za obradu slike Image Pro 3.0, sistem bez zatvarača (HSIS – Shutterless Image System) i Sync Pro algoritam obezbeđuju gladak i detaljan prikaz slike uz minimalno kašnjenje. Zahvaljujući velikom 0,49" AMOLED ekranu, model NE25 pruža impresivan vizuelni doživljaj i jasan prikaz slike u svim uslovima rada. Prikaz slike: Ekran: 0.49 inča AMOLED Paleta boja: Crna, Bela, Crvena, Fuzija, Zelena Image Pro 3.0 + Sync Pro (smanjen lag slike) Termalni modul: Tip senzora: VOx uncooled FPA Rezolucija: 256 × 192 Pixel pitch: 12 μm Spektralni opseg: 8–14 μm NETD: ≤ 18 mK Frame rate: 50 Hz Optika: Objektiv: 25 mm Blenda: F1.0 Fokus: ručni (focus ring) Domet detekcije: do ~1200 m Prikaz i uvećanje: Osnovno uvećanje: 3.5× Digitalni zoom: do ~24.5× (kontinuirani) Vidno polje (FOV): 7.0° x 5.3° / 12.2m x 9.3m Funkcije: Wi-Fi: da Snimanje: video / foto / audio Recoil-activated recording PiP (picture-in-picture) Zeroing profili: do 5 Memorija: Interna memorija: 64 GB Napajanje: Tip baterije: 1× interna + 1× 18650 eksterna Autonomija: ~ 9.5 h (zavisno od režima) Punjenje: USB-C (QC3.0) Mehaničke karakteristike: Zaštita: IP67 Otpornost na trzaj: ~1000 g / 0.4 ms Radna temperatura: -30°C do +55°C Montaža: 30 mm Dimenzije i masa: Dimenzije: ~345.6 × 86 × 56.1 mm Težina: ~540 g	849,00	707,50
---	-------	---	--------	--------

NH25L Neos  	10447	NH25L Neos HIKMICRO NEOS NH25L termalni nišan poseduje rezoluciju od 320 × 240 piksela i opremljen je termalnim detektorom sa NETD vrednošću manjom od 18 mK, što omogućava izuzetnu osetljivost i prepoznavanje sitnih temperaturnih razlika. Napredni algoritam za obradu slike Image Pro 3.0, sistem bez zatvarača (HSIS – Shutterless Image System) i Sync Pro algoritam omogućavaju korisnicima da dobiju glatku, detaljnu sliku sa manjim kašnjenjem prikazaSa većim 0,49" AMOLED ekranom, model NH25L pruža impresivan doživljaj gledanja i jasniji prikaz slike.Ugrađeni laserski daljinomer i funkcija balističkog proračuna doprinose preciznijem nišanjenju i tačnijem gađanju. Prikaz slike: Ekran: 0.49 inča AMOLED Palete boja: Crna, Bela, Crvena, Fuzija, Zelena Image Pro 3.0 + Sync Pro (smanjen lag slike) Termalni modul: Tip senzora: VOx uncooled FPA Rezolucija: 320 × 240 Pixel pitch: 12 μm Spektralni opseg: 8–14 μm NETD: ≤ 18 mK Frame rate: 50 Hz Optika: Objektiv: 25 mm Blenda: F1.0 Fokus: ručni (focus ring) Domet detekcije: do ~1200 m Prikaz i uvećanje: Osnovno uvećanje: 3.5× Digitalni zoom: do ~24.5× (kontinuirani) Vidno polje (FOV): 7.0° x 5.3° / 12.2m x 9.3m Funkcije: LRF (laserski daljinomer): do ~1000 m, ±1 m Balistički kalkulator: da Wi-Fi: da Snimanje: video / foto / audio Recoil-activated recording PIP (picture-in-picture) Zeroing profili: do 5 Memorija: Interna memorija: 64 GB Napajanje: Tip baterije: 1× interna + 1× 18650 eksterna Autonomija: ~ 9 h (zavisno od režima) Punjenje: USB-C (QC3.0) Mehaničke karakteristike: Zaštita: IP67 Otpornost na trzaj: ~1000 g / 0.4 ms Radna temperatura: -30°C do +55°C Montaža: 30 mm Dimenzije i masa: Dimenzije: ~345.6 × 86 × 75.8 mm Težina: ~550 g	1099,00	915,83
---	-------	--	---------	--------